

SURGE ANTICIPATOR RELIEF

/ REMOTE SENSE

SERIES NO:- 203

ADJUSTMENT RANGE:

*-Low pressure : standard 20-200 psig,
optional 0-30 psig.*

*-High pressure : standard 20-200 psig,
optional 0-30, 100-300 psig*

QUICK SIZING:

Valve size one or two sizes smaller than main line.

POINTS TO CONSIDER:

- Refer to Engineering Data - Flow Capacity Chart

COMPONENTS

- 1. Main Valve*
- 2. Adj. Closing Speed*
- 3. Adj. Opening Speed*
- 4. Relief Control*
- 5. Low Pressure Control*
- 6. Drain Valve*
- 7. Test Valves*
- 8. Pressure Gauge*
- P. Position Indicator*

ACCESSORIES

Located as indicated

Included as marked

- Isolation Cocks*
- Y Strainer*
- Limit Switch*

<i>VALVE SIZE</i>	<i>1 1/4"</i>	<i>1 1/2"</i>	<i>2"</i>	<i>2 1/2"</i>	<i>3"</i>	<i>4"</i>	<i>6"</i>	<i>8"</i>	<i>10"</i>	<i>12"</i>	<i>14"</i>	<i>16"</i>
<i>Maximum Continuous Flow Rate GPM(Water)</i>	93	125	208	300	460	800	1800	3100	4900	7000	8500	11000
<i>Maximum Intermittent Flow Rate GPM(Water)</i>	210	280	460	650	1000	1800	4000	7000	11000	16000	19000	25000

Nutech Valves

37, Shreeji Industrial Estate, Raypur Mill Compound, Saraspur, Ahmedabad - 24

Ph..(O) :- 079 - 29292112, 32923375 Fax :- 079 - 22133122

E-Mail :- sales@nutechvalves.com Website :- www.nutechvalves.com

AN ISO 9001:2000 Certified Co.